




DIN 6350



3274, 3275, 3574, 3575



3204 3205-800


PLAIN BACK MOUNTING

Chuck size A		80	85 ¹⁾	100	110	125	140	160
B	type 3500, 3700	44	-	50	-	59,5	-	68
	the others	44	44	50	50	56	60	64,5
B1	type 3500, 3700	-	-	-	-	64,3	-	72,8
	the others	-	-	-	-	60,8	64,8	69,3
C		3	3	3	4	4	4	4
D H7		56	62	70	80	95	105	125
E		16	18	20	27	32 35,5 ³⁾	40	42
F		67	72	83	95	108	120	140
G ²⁾		3xM6	-	3xM8	3xM8	3xM8	3xM8	6xM10
H		32	43	42	42	51	51	70
J		13	13	17	17	20	20	32
K		-	-	-	-	56	56	67
L		-	-	-	-	40	40	43
P		3xM6	3xM6	3xM8	-	3xM8	-	3xM10
weight approx. kg		1,5	1,9	2,8	3,4	5,0	6,0	10,0

Chuck size A		200	250	315	400	500	630	800
B	type 3500, 3700	78	89	97,2	109	119	129	-
	the others	75	85	94	105	120	135	159
B1	type 3500, 3700	82,8	92,8	101,3	116,8	129,8	140,3	-
	the others	79,8	88,8	99,1	113,8	130,8	146,3	170,3
C		4	5	5	5	5	7	20
D H7		160	200	260	330	420	545	450
E		55	76	103	136	190	252	320
F		176	224	286	362	458	586	368,3
G ²⁾		6xM10	6xM12	6xM16	6xM16	6xM16	6xM16	-
H		85	105	125	145	180	225	225
J		29	34	43	55	60	70	70
K		80	95	110	127	127	127	127
L		45	53	57	67	79	87	87
P		3xM10	3xM12	3xM16	3xM16	6xM16	6xM16	6xM24
weight approx. kg		17,5	29	50	85	145,0	250,0	402

¹⁾ for type 3274 chucks, ²⁾ 3 holes for types 3274, 3275, 3574, 3575, ³⁾ for type 3500, 3700

DIN 55026



FORM A MOUNTING

Chuck size A		160	200				250			315		
Short taper 1:4		5	4	5	6		5	6	8	6	8	
B	type 3500, 3700	68	78				89			96,2		
	the others	81,5	91				103,5			117,7		
B1	type 3500, 3700	72,8	82,8				92,8			101,3		
	the others	86,3	95,8				107,3			122,8		
D	min	82,563	63,513	82,563	106,375	82,563	106,375	139,719	106,375	139,719		
	max	82,578	63,526	82,578	106,390	82,578	106,390	139,734	106,390	139,734		
E		42	42	42	55	76	55	76	103	80		
F1		61,9	-	61,9	82,6	-	82,6	111,1	-	111,1		
G1		M10	-	M10	M12	-	M12	M16	-	M16		
F		-	82,6	-	-	104,8	-	-	133,4	-		
G		-	M10	-	-	M10	-	-	M12	-		
qty. of mounting screws	3-jaw	3	3				3	6			6	
	4-jaw	4	4				4			8	4	
weight approx. kg		10,0	19,0				32,0			55,0		

Chuck size A		400			500		630		800		
Short taper 1:4		6	8	11	8	11	11	15	11	15	20
B	type 3500, 3700	108			119		129		-		
	the others	128,5			146		165		159		
B1	type 3500, 3700	116,8			129,8		140,3		-		
	the others	137,3			157,3		175,8		191,3		
D	min	106,375	139,719	196,869	139,719	196,869	196,869	285,775	196,869	285,775	412,775
	max	106,390	139,734	196,887	139,734	196,887	196,887	285,795	196,887	285,795	412,802
E		103	136	130	136	190	190	190*	190		320
F1		-	-	165,1	-	-	-	-	-	247,6	-
G1		-	-	M 20	-	-	-	-	-	M 24	-
F		133,4	171,4	-	171,4	235	235	330,2	235	-	368,3
G		M12	M16	-	M16	M20	M20	M24	M20	-	M24
qty. of mounting screws	3-jaw	6			6		6		6		
	4-jaw	8	8	4	4	8	-		-		
weight approx. kg		92,0			160,0		285,0		384,0		

* 252 for chuck type 3500